



SEASCAPE 4%

SPECIFICATION

Fire Retardant: NFPA 701-10 TM#1, California U.S. Title 19 CAN/ULC-S109-03 Small & Large Flame Test

Fabric Width: 98" (250 cm), 122" (310 cm)

Roll Length: 23 yds

Composition: 33.6% fiberglass / 59.6% vinyl 6.8% polyester

Openness Factor: 4%

Thickness: 0.037" (0.93 mm) ± 5%

Weight: 18.9 oz / yd² (642 g / m²) ± 5%

Cutting: Ultrasonic, Crush, Cold

Fabric Style: Plain Weave

UV Blockage: Approximately 96%

Bacterial Resistance: ASTM E2180, ASTM G21

Acoustical Performance: NRC: 0.10, SAA: 0.12

Environmental Benefits: RoHS - Lead Free



Fabrication Methods:

Cutting: cold, ultrasonic or crush

Welding: radio frequency, high frequency, impulse, hot air, wedge.

May require the use of welding tape.

Care & Cleaning Instructions:

Remove dust with vacuum cleaner or compressed air. Do not scrub.

Do not use solvents or any abrasive substance which might damage the coating of the fabric.

Clean with a sponge or a soft brush dipped in soapy water using mild detergent.

Rinse with clean water. Leave the blind down until completely dry.

You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.




Dead Sea



Sisal



Smoky Quartz



Spice

