



## 4000 Net 3% Openness


Solar Screen




Dove/Dove




Dove/Sand




White/White




White/Beige




White/Gray




Beige/Beige



Beige/Gray



Charcoal/Charcoal



Charcoal/Bronze

## Specifications

<b>Composition</b>	27% Polyester, 73% PVC
<b>Openness</b>	3%
<b>Width(s)</b>	98.4" (2.5m), 118" (3m)
<b>Length</b>	33 yd/roll (30m)
<b>Weight</b>	16.07oz/yd <sup>2</sup> (545 g/m <sup>2</sup> )
<b>Thickness</b>	0.029in (.75mm)
<b>Fire Classification</b>	NFPA 701, M1, B1, B2, CA Title 19
<b>Railroadable</b>	Yes
<b>Cleaning</b>	Wipe clean with warm soapy water and damp cloth.

### Applications



PANEL



ROLLER

### Features



ENERGY  
SAVING



FRAGRANCE  
FREE



LIMITED  
LIFETIME  
WARRANTY



SCREEN

### Certifications



ISO  
14001

ISO  
9001

OEKO-TEX®  
STANDARD 100  
by Hohenstein



PHTHALATE  
FREE



FR



LEAD FREE



HEALTH PRODUCT  
DECLARATION



FORMALDEHYDE  
FREE



ANTI-  
BACTERIAL

