



STAR / BLACKOUT

SPECIFICATION

Fabric Star Blackout

Composition 100% Polyester

Width 92.5"

Weight 9.44 oz/yd²

Thickness 0.016"

Finish Pigmented acrylic coating. White acrylic backing.

Light fastness Min. 5-6

Light transmission Blackout

Shrinkage Max 1%.


Approx. roll length 27.3 yards

No flame retardant treatment


CLEANING INSTRUCTIONS

Vacuum cleaning and/or gentle wiping with a sponge and a soft detergent. Do not soak, do not use any other solvents and do not rub.

Transparent



Pure



Ashes



Luna



Dust

Light fastness: Tested according to SS ISO 105-B02. Best value 8. Natural fibers fade when unbleached.

Shrinkage: Values are valid at normal use and cleaning in accordance with the instructions. Please note that natural fibers shrink depending on climate.

Cutting: Cold cutting of fabrics is recommended.

Non- PVC: Does not contain PVC.

Sustainability: Environmental declaration and energy values are available on request.

Optical Information: Tested according to ISO 7724 Part 1, 2, 3. Textile materials are by nature slightly different from one batch to another. The values can have a variance of +/- 5%. The human eye will not conceive this as a difference. Solar values are presented here, light values available on request. We indicate the values of the base fabric for printed items, as this have the most influence on the optical values.

