



CALYPSO / TRANSLUCENT

SPECIFICATION

Fire Retardant: NFPA 701-10 TM#1, California U.S. Title 19 CAN/ULC-S109 Small & Large scale

Fabric Width: 118"

Roll Length: 33 yds

Composition: 100% polyester

Openness Factor: < 1%

Thickness: 0.021" (0.52 mm) \pm 10%

Weight: 5.90 oz / yd² (200 g / m²) \pm 10%

Cutting: Ultrasonic, Crush, Cold

UV Blockage: Approximately 99%

Fabric Style: Fancy Weave

Bacterial Resistance: ASTM E2180

Acoustical Performance: NRC: 0.05, SAA: 0.05

Environmental Benefits: RoHS - Lead Free



Fabrication Methods:

Cutting: cold, ultrasonic or crush

Welding: radio frequency, high frequency, impulse, hot air, wedge. May require the use of welding tape. Please contact Mermet for more information regarding our welding tape product line

Care & Cleaning Instructions:

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. For spot removal a natural or dry cleaning sponge may be used.



Frost



Orchid



Anew



Gem



Java



Seahorse



Stargazer

