

# LUSTRE / BLACKOUT

## SPECIFICATION

**Fabric** Lustre Blackout  
**Composition** 100% polyester  
**Width** 76.7 inches  
**Weight** 8.26 oz/yd2  
**Thickness** 0,014 inches  
**Finish** Dyed or color coated. White acrylic backing.  
**Light fastness** Min. 5-6 (SS ISO 105-B02. Best value 8)  
**Light transmission** Blackout  
**Shrinkage** Max 1%.  
**Approx. roll length** 32.8 yards  
**No flame retardant treatment**




**Fabric** Lustre Blackout FR  
**Composition** 100% polyester  
**Width** 76.7 inches  
**Weight** 8.26 oz/yd2  
**Thickness** 0,014 inches  
**Finish** White or dyed. White acrylic backing.  
**Light fastness** Min. 5-6 (SS ISO 105-B02. Best value 8)  
**Light transmission** Blackout  
**Shrinkage** Max 1%.  
**Approx. roll length** 32.8 yards  
**Flame Retardant** Phosphorous based flame retardant treatment  
**Fire Resistant Standard** DIN 4102-1 class B1

## CLEANING INSTRUCTIONS

Vacuum cleaning and/or gentle wiping with a sponge and a soft detergent. Do not soak, do not use any other solvents and do not rub.

Blackout



Reseda



Deep Ocean



Gravity

