

Regulatory Compliance



Do not dispose of in general waste.
Please recycle batteries and damaged electrical products appropriately.

Specifications:

Model	AUTOMATE Rechargeable Battery Pack-12V
Model #	MTBPCKR-28
Input Voltage	12.6 VDC
Input Current	1 A
Typical Voltage	12 VDC
Nominal Voltage	10.8 V
Nominal Capacity:	2600 mAh
Charging time	≈ 6 Hours
IP Rating	N/A
Limit Switch Type	N/A
Radio Frequency	N/A
Battery Size/Type	1-1/4"×1-1/4"×10" / Li-ion Rechargeable
Temp Working	32°F to 140°F (0°C to 60°C)
Insulation Class	N/A

Rollease Acmeda declares that this equipment is compliance with the essential requirements and is tested to comply with:

UL 2595	General Requirements for Battery-Powered Appliances
CSA C22.2 No. 0.23	General Requirements for Battery-Powered Appliances
UN38.3	UN Model Regulations, Manual of Test and Criteria

Battery Safety Statement

Product safety is considered integral to Rollease Acmeda's product offering.

As such, all products containing lithium-ion batteries are manufactured, tested and certified to stringent standards.

Testing is conducted to cover all aspects of the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3, including:

- Altitude Simulation
- Thermal Test
- Vibration
- Shock
- External Short Circuit
- Impact / Crush
- Overcharge
- Forced Discharge

Additionally, all battery products assemblies utilize an integrated charge management circuit which protects against over or under charging. This circuit also enables individual cell balancing which ensures the longevity and integrity of the entire battery pack.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment